



J&A (International) Limited
THE GARMENT DECORATION SPECIALISTS

TECHNICAL DATASHEET

Clear Pockets



www.ja-int.com | +44 (0)1790 752 757

J&A (International) Ltd. Insignia House, Vale Road, Spilsby, Lincolnshire PE23 5HE

Clear Pockets



TECHNICAL DATASHEET

www.ja-int.com

ADHESIVE MATERIAL

APPLICATION

Temperature (°C):	165°C		
Time:	15 seconds		
Pressure:	Low		
High:	56.8 - 71.1 Psi	3.9 - 4.9 Bar	4.0 - 5.0 Kg/Cm2
Medium:	42.6 - 56.8 Psi	2.9 - 3.9 Bar	3.0 - 4.0 Kg/Cm2
Low:	28.4 - 42.6 Psi	2.0 - 3.9 Bar	2.0 - 3.0 Kg/Cm2

COMPOSITION

Adhesive:	Polyester based
-----------	-----------------

LAUNDERING

Wash:	Excellent up to 60°C
Dry:	Follow garment drying instructions

STORAGE

Store in a cool dry environment away from direct sunlight

HEALTH & SAFETY

This product is identified as Non-Hazardous to the end user
No personal protection equipment is required in handling and storage
Not vegan friendly

POCKET MATERIAL

SEMI RIGID PVC - GLASS CLEAR POLISHED EMOSS

Thickness (mym)	140 +/- 5%
Handle (phr):	33 +/- 1
Cold Crack (oC):	-10 C MAX

SEMI RIGID PVC - GLASS CLEAR POLISHED EMOSS

Tensile Strength:	22MPa
Elongation At Break:	200%
Tear Strength:	190N/mm
Dimensional Stability	1.5% max 5min/70 C

**Any fumes created by this transfer during application are harmless. However, modern garment materials can be coated and finished in many different ways; some of which may alter their application and health & safety requirements. We recommend thorough checking and testing of any garment material to determine the correct requirements before application. We recommend that any doubts in the wash performance and application conditions of a product should be removed by performing tests under your own conditions.