

## TECHNICAL DATASHEET

# Trimax Kolormax



## Trimax Kolormax



### **TECHNICAL DATASHEET**

www.ja-int.com

#### **APPLICATION**

Temperature (°C):	140-160°C			
Time:	10-12 seconds			
Carrier Release:	Hot peel			
Pressure:	Medium			
High:	56.8 - 71.1 Psi	3.9 - 4.9 Bar	4.0 - 5.0 Kg/Cm2	
Medium:	42.6 - 56.8 Psi	2.9 - 3.9 Bar	3.0 - 4.0 Kg/Cm2	
Low:	28.4 - 42.6 Psi	2.0 - 3.9 Bar	2.0 - 3.0 Kg/Cm2	

#### **COMPOSITION**

Carrier:	Coated Polyester Sheeting
Ink:	Digital & Water Based
Adhesive:	Polyester

#### **ENVIRONMENTAL / RECYCLING**

Polyester carrier:	Non-recylable
Vegan-Friendly:	No
All inks:	Compostable

#### **CERTIFICATION**

Oeko-Tex:	Standard 100 (Class 2)
Flame Retardant:	EN ISO 11611 & EN ISO 11612

#### **LAUNDERING**

Suitable for 30 domestic wash processes up to 60°C, with fabric softener and a tumble dry finish.

This product is not suitable for dry-cleaning, and it cannot withstand bleach.

This must be ironed on the reverse.

#### **STORAGE**

Store in a cool dry environment away from direct sunlight

#### **HEALTH & SAFETY**

This product is identified as Non-Hazardous to the end user No personal protection equipment is required in handling and storage

<sup>\*\*</sup>Any fumes created by this transfer during application are harmless. However, modern garment materials can be coated and finished in many different ways; some of which may alter their application and health & safety requirements. We recommend thorough checking and testing of any garment material to determine the correct requirements before application. We recommend that any doubts in the wash performance and application conditions of a product should be removed by performing tests under your own conditions.